

Revision Date: January 2022

Phone: +39 0362 1547305

Fax: +39 039 8942754

Version: 1.2

GC D HF 41 CE

HALOGEN-FREE FLAME RETARDANT BLEND

GC D HF 41 CE is a halogen-free flame retardant formulation developed for styrenic resins. GC D HF 41 CE provides excellent flame retardant properties and allows high processing temperature.

GC D HF 41 CE contains a synergist that enables a decrease in the total amount of flame retardant content in final compound. GC D HF 41 CE is a highly concentrated product.GC D HF 41 CE meets RoHS legislation and does not contain SVHC substances. Recommended dosage is 2-8% depending on the used polymer.

PHYSICAL-CHEMICAL PROPERTIES

Appearance White to yellowish pellets

Density at 25°, C g/cm3 1.3 ± 0.3 Volatiles,% 0.5 max

HANDLING AND STORAGE: The processing and use of GC D HF 41 CE requires adequate technical and

professional knowledge. Please consult safety data sheet for further handling,

storage and toxicity information.

GC D HF 41 CE has to be stored in tightly sealed original container in a cool and

well-ventilated area, away from direct sunlight.

PACKAGING: Standard packaging size of GC D HF 41 CE is in 25 Kg.

IMPORTANT NOTE Some plastic additives, fillers or pigments can have a significant influence on

> the properties of the end product. Before using this product, please be informed. Machine stop at high temperature could create degradation of

polymers. Please clean with neutral polymers.

DISCLAIMER:

Information contained in this document is provided to the best of our knowledge and is considered true as per revision date. We do not accept any liability for loss and damage that may occur from the improperly use of this information and for the use against the safety legal requirements and patent rights. This specification does not release the customer from the obligation to check the product as to its suitability for intended area of usage.