



Revision Date: June 2018
Version: 1.1

STARAID PE OL 20

Oleamide Masterbatch

STARAID PE OL 20 is a dispersion of an oleamide in polyethylene which functions as a slip agent. STARAID PE OL 20 does not contain a mineral filler and is recommended for those applications where a reduction of the coefficient of friction is required. The fast migration offers an immediate slip performance.

Recommended Dosage: 0,2% - 0,5%

PHYSICAL-CHEMICAL PROPERTIES

Appearance	Granular
Colour	Milky white or light yellow
Oleamide, %	20 ± 1
Melting Point, °C	> 100°C
Moisture, ppm	Max 2000

HANDLING AND STORAGE: The processing and use of STARAID PE OL 20 requires adequate technical and professional knowledge. Please consult safety data sheet for further handling, storage and toxicity information.

STARAID PE OL 20 has to be stored in tightly sealed original container in a cool and well-ventilated area, away from direct sunlight.

PACKAGING: Standard pack size of STARAID PE OL 20 is 25 Kg in plastic bags.

IMPORTANT NOTE

Some plastic additives, fillers or pigments can influence significantly the flame retardant properties of the end product. Before using this product, please be informed. Machine stop at high temperature could create degradation of polymers. Please clean with neutral polymers.

DISCLAIMER:

Information contained in this document is provided to the best of our knowledge and is considered true as per revision date. We do not accept any liability for loss and damage that may occur from the improper use of this information and for the use against the safety legal requirements and patent rights. This specification does not release the customer from the obligation to check the product as to its suitability for intended area of usage.